


Orion Launch Abort Vehicle Separation Analysis using **OVERFLOW**

****DRAFT****

Prepared by:
Tom Booth
Jacobs Technology
NASA JSC/EG3


****DRAFT****

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




Overview

- Background
- Purpose
- Geometry
- Grids
- OVERFLOW inputs
- Convergence study
- Results
- Conclusions




DRAFT

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




Background

- We want to ride on rockets
- Sometime rockets blow up
- Therefore, we need a launch abort system



DRAFT

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




Purpose

- Calculate separation effects
 - Aerodynamic database
 - Integrated forces/moments
 - Aerodynamic loads database
 - Pressure distributions
 - Line loads




****DRAFT****


Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




Geometry



Launch Abort Vehicle




Abort Test Booster (ATB)






DRAFT

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




Overset Grids

- Chimera Grid Scripts
- Pegasus5
- 50 grids
 - 93.5 million grid points



DRAFT

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




Assumptions

- Steady state
- Multiple species
- Calorically perfect gas exhaust
- Single phase flow



DRAFT


Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov



General Run Strategy


- 3 levels of grid sequencing
 - 2000 iterations/level
- Steady state until converged
- Time accurate
 - If needed






Overflow Inputs

- Constant CFL (ITIME=4)
- SST turbulence model (NQT=205)
- Numerical methods
 - HLLC (IRHS=5)
 - 32-bit SSOR (ILHS=16)
- No Compressibility Correction (ICC=0)




Computational Resources

- NASA Advanced Supercomputing (NAS) division
 - Pleiades
 - Columbia
 - CPU hours used:
 - 907,000 hours




DRAFT

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




Convergence Study

- Investigate force/moment sensitivity
 - Steady State
 - Time Accurate
- Convergence tolerance
 - $\frac{1}{2}^\circ$ AOA for C_m - α at trim




Residual





****DRAFT****

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov



Force/Moment




- Coarse Grid
- Medium Grid
- Steady State
- Time Accurate

Within tolerances

- Steady State Avg.
- Time Accurate Avg.
- Convergence Tol.

DRAFT

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




WTT Comparison

LAV separation from an ATB/SM


AR-107 CFD: Mach 1.71, offset 0.7, AMCT=2.07

AR-104 CFD: Mach 1.7, offset 0.7, AMCT=2.0


60-AA WTT: Mach 1.60, AMCT=2.8




CFD matched trend with WTT



CFD had small AMCT delta




- AR107 $\alpha=-5$ (red solid line with circles)
- AR107 $\alpha=0$ (purple dashed line with crosses)
- AR107 $\alpha=5$ (green dashed line with stars)
- AR104 $\alpha=-5$, no ATB (red dashed line with circles)
- AR104 $\alpha=0$, no ATB (purple dashed line with crosses)
- AR104 $\alpha=5$, no ATB (green dashed line with stars)
- 60-AA $\alpha=0$ (purple circles)



Results

LAV-ATB separation at Mach 0.9


Preliminary Data



Largest
discrepancy
at X/D 0.05

DRAFT


Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov



Results


LAV-ATB separation at Mach 0.9

Preliminary Data



DRAFT


Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov



Results

LAV-ATB separation at Mach 0.9


Preliminary Data



Not sure of reason for reversal of trends....fix before final pp



DRAFT

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




Results

Mach 0.9
Alpha 0
AMCT 3.0
X/D 0.05




****DRAFT****

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov




Results

CFD - PSP



****DRAFT****

Tom Booth, (281) 483-3234,
thomas.booth@nasa.gov



Conclusions

- Steady state assumption valid
 - Avg. integrated loads
 - Investigate effect on instantaneous pressure distribution
- Drag is affected until roughly $7 X/D$